

## MVT 15系列振动电机

三相

| 描述          |    | 认证                                                                                |                                                                                   | 机械特性                                                                              |                                                                                   |        |      |       |       | 电气特性 |      |      |      |           |           |
|-------------|----|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------|------|-------|-------|------|------|------|------|-----------|-----------|
| 型号          | 机座 |  |  |  |  | 静扭矩    |      | 振动力   |       | 重量   |      | 输出功率 |      | 最大电流      |           |
|             |    |                                                                                   |                                                                                   |                                                                                   |                                                                                   | in-lbs |      | lbs   |       | lbs  |      | HP   |      | A         |           |
|             |    |                                                                                   |                                                                                   |                                                                                   |                                                                                   | 50Hz   | 60Hz | 50Hz  | 60Hz  | 50Hz | 60Hz | 50Hz | 60Hz | 400V 50Hz | 460V 60Hz |
| MVT 15/3500 | 70 |  |  |  |  | 119    | 82,7 | 7590  | 7700  | 372  | 348  | 2,50 | 2,50 | 4,00      | 3,50      |
| MVT 15/5000 | 80 |  |  |  |  | 173    | 121  | 11015 | 11051 | 517  | 484  | 3,50 | 3,50 | 5,40      | 4,85      |
| MVT 15/7900 | 90 |  |  |  |  | 274    | 191  | 17446 | 17446 | 669  | 636  | 4,30 | 4,70 | 6,50      | 6,20      |

\* 工作扭矩=2x静扭矩。静扭矩=不平衡量。  
230V, 60HZ的电流是460V, 60HZ的两倍。  
1in=25.4mm 1lbs=0.4532kg 1kg.mm=11.43lbs.in

\* MVT 15/5000和MVT 15/7900 需定制，客户  
提供所需外形尺寸和安装地脚尺寸。



I 类C和D组温度等级T3 (200°C)  
文件号: E129825.



产品由IECEX Scheme批准:  
Ex d IIB T140° C Gb. IEC 60079-0, IEC 60079-1  
证书号: IECEX UL 11.0043X