


Fig. W



6 极 - 1000/1200 rpm

代码	型号	描述	尺寸	G	轴扭矩				机械特性				重量				最大输入功率				电气特性				I _h /In
					50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	400 V	400 V	50 Hz	60 Hz	50 Hz	60 Hz	
602283	MVSS 10/40-S02	10	•		30.1	30.1	35	49	0.33	0.47	12.5	12.5	120	135	0.30	0.30	1.90	2.07			50 Hz	60 Hz	50 Hz	60 Hz	
602284	MVSS 10/100-S02	10	•		84.2	84.2	94.3	136	0.93	1.33	15.8	15.8	120	135	0.30	0.30	1.90	2.07			50 Hz	60 Hz	50 Hz	60 Hz	
602285	MVSS 10/200-S02	20	•		163	163	183	264	1.80	2.59	22.5	22.5	185	205	0.50	0.50	2.72	3.10			50 Hz	60 Hz	50 Hz	60 Hz	
602286	MVSS 10/310-S02	30	•		286	209	321	338	3.15	3.32	32.0	30.7	350	380	0.72	0.68	2.63	2.79			50 Hz	60 Hz	50 Hz	60 Hz	
602287	MVSS 10/550-S02	35	•		457	457	512	737	5.02	7.23	43.5	43.5	350	380	0.75	0.68	2.53	3.68			50 Hz	60 Hz	50 Hz	60 Hz	
602288	MVSS 10/810-S02	40	•		723	561	809	905	7.84	8.88	54.0	52.6	680	760	1.40	1.35	2.79	3.33			50 Hz	60 Hz	50 Hz	60 Hz	
602289	MVSS 10/1110-S02	50	•		1012	715	1132	1151	11.1	11.3	67.0	59.5	750	750	1.65	1.50	3.33	4.13			50 Hz	60 Hz	50 Hz	60 Hz	
602290	MVSS 10/1400-S02	50	•		1274	904	1424	1495	14.0	14.3	78.0	71.0	950	1000	2.10	2.00	3.60	4.30			50 Hz	60 Hz	50 Hz	60 Hz	
602291	MVSS 10/1610-S02	60	•		1464	962	1638	1549	16.1	15.2	94.0	83.0	1100	1300	2.20	2.20	4.21	4.05			50 Hz	60 Hz	50 Hz	60 Hz	
602292	MVSS 10/2100-S02	60	•		1927	1318	2154	2121	21.1	20.8	105	93.0	1500	1700	3.00	2.90	4.50	4.02			50 Hz	60 Hz	50 Hz	60 Hz	
602293	MVSS 10/2610-S02	70	•		2326	1706	2601	2747	25.5	26.9	130	116	1960	2100	4.10	3.75	5.35	5.60			50 Hz	60 Hz	50 Hz	60 Hz	
602294	MVSS 10/3000-S02	70	•		2690	1940	3007	3124	29.5	30.6	145	130	2200	2400	4.50	4.30	4.35	4.81			50 Hz	60 Hz	50 Hz	60 Hz	

型号	Fig.	尺寸(mm)														电缆进口螺纹
		A	B	C	D	E	øG	N'	F	H	I	L	M	N		
MVSS 10/40-S02	W	255	176	152	90	125	13	4	12	73	54	124	122	141	M20x1.5	
MVSS 10/100-S02	W	295	176	152	90	125	13	4	12	73	74	124	122	141	M20x1.5	
MVSS 10/200-S02	W	340	200	167	105	140	13	4	15	82.5	91	143	137	160	M25x1.5	
MVSS 10/310-S02	W	378	211	205	120	170	17	4	17	93.5	98	168	160	182	M25x1.5	
MVSS 10/550-S02	W	434	232	205	120	170	17	4	20	104.5	117	181	162	203	M25x1.5	
MVSS 10/810-S02	W	490 (50Hz) 601 (60Hz)	245	230	140	190	17	4	25	116	129 (60Hz) 135 (60Hz)	201	180	225	M25x1.5	
MVSS 10/1110-S02	W	560 (50Hz) 660 (60Hz)	245	230	140	190	17	4	25	116	164 (60Hz) 179 (60Hz)	201	180	225	M25x1.5	
MVSS 10/1400-S02	W	560	245	230	140	190	17	4	25	116	164	201	180	225	M25x1.5	
MVSS 10/1610-S02	W	601 (50Hz) 660 (60Hz)	285	275	155	225	22	4	30	135	169 (60Hz) 184 (60Hz)	231	205	253	M25x1.5	
MVSS 10/2100-S02	W	601	285	275	155	225	22	4	30	135	169	231	205	253	M25x1.5	
MVSS 10/2610-S02	W	657 (50Hz) 689 (60Hz)	323	310	155	255	23.5	4	35	155	173 (60Hz) 193 (60Hz)	269	215	295	M25x1.5	
MVSS 10/3000-S02	W	705	323	310	155	255	23.5	4	35	155	197.5	269	215	295	M25x1.5	

8 极 - 750/900 rpm

代码	型号	描述	尺寸	G	轴扭矩				机械特性				重量				最大输入功率				电气特性				I _h /In
					50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	400 V	400 V	50 Hz	60 Hz	50 Hz	60 Hz	
602561	MVSS 075/150-S02	20	•		163	163	104	149	1.02	1.46	22.5	22.5	230	250	0.85	0.76	2.13	2.11			50 Hz	60 Hz	50 Hz	60 Hz	
602562	MVSS 075/250-S02	30	•		286	286	181	260	1.76	2.55	32.0	32.0	350	380	1.10	1.05	2.03	2.29			50 Hz	60 Hz	50 Hz	60 Hz	
602563	MVSS 075/400-S02	35	•		457	457	288	415	2.83	4.07	43.5	43.5	280	300	0.60	0.58	1.73	2.50			50 Hz	60 Hz	50 Hz	60 Hz	
602564	MVSS 075/660-S02	40	•		723	723	456	656	4.47	6.44	54.0	54.0	400	450	1.20	1.20	2.38	2.58			50 Hz	60 Hz	50 Hz	60 Hz	
602565	MVSS 075/910-S02	50	•		1012	1012	637	917	6.25	9.00	67.0	67.0	400	500	1.40	1.30	2.38	2.85			50 Hz	60 Hz	50 Hz	60 Hz	
602566	MVSS 075/1310-S02	60	•		1464	1464	922	1327	9.04	13.0	94.0	94.0	950	1100	2.20	2.20	2.63	3.41			50 Hz	60 Hz	50 Hz	60 Hz	
602567	MVSS 075/2110-S02	70	•		2326	2326	1463	2107	14.4	20.7	130	130	1500	1790	4.10	4.20	3.55	2.95			50 Hz	60 Hz	50 Hz	60 Hz	

型号	尺寸(mm)															电缆进口螺纹
	Fig.	A	B	C	D	E	øG	N'	F	H	I	L	M	N		
MVSS 075/150-S02	W	340	200	167	105	140	13	4	15	82.5	91	143	137	160	M25x1.5	
MVSS 075/250-S02	W	378	211	205	120	170	17	4	17	93.5	98	168	160	182	M25x1.5	
MVSS 075/400-S02	W	434	232	205	120	170	17	4	20	104.5	117	181	162	203	M25x1.5	
MVSS 075/660-S02	W	490	245	230	140	190	17	4	25	116	129	201	180	225	M25x1.5	
MVSS 075/910-S02	W	560	245	230	140	190	17	4	25	116	164	201	180	225	M25x1.5	
MVSS 075/1310-S02	W	601	285	275	155	225	22	4	30	135	169	231	205	253	M25x1.5	
MVSS 075/2110-S02	W	657	323	310	155	255	23.5	4	35	155	173.5	269	215	295	M25x1.5	

*工作扭矩→2秒启动